

Panasonic Compressor and Motor R-Series Rotary Compressor Specification Table

Series			R						
Model			R7	R8	R9	R10	R11	R12	R13
Rated Output W			360.00	400.00	470.00	470.00	500.00	550.00	600.00
Displacement CC/rev			7.30	8.00	9.20	9.50	10.30	11.40	12.40
Cooling Capacity (Nominal)	60HZ	W	1,475.00	1,640.00	1,880.00	1,910.00	2,055.00	2,330.00	2,505.00
		(Kcal/h)	1,269.00	1,410.00	1,617.00	1,643.00	1,767.00	2,004.00	2,154.00
		(BTU)	5,033.00	5,596.00	6,415.00	6,518.00	7,013.00	7,951.00	8,548.00
	50HZ	W	1,215.00	1,315.00	-	1,580.00	1,730.00	1,895.00	2,080.00
		(Kcal/h)	1,045.00	1,131.00	-	1,359.00	1,488.00	1,630.00	1,789.00
		(BTU)	4,146.00	4,487.00	-	5,392.00	5,904.00	6,467.00	7,098.00
Weight Kg			8.40	8.50	8.80	8.40	7.80	8.90	9.00
Dimension (Nominal)	A	mm	210.00	210.00	215.00	210.00	200.00	220.00	220.00
	B	mm	90.00	90.00	90.00	90.00	90.00	90.00	90.00
	C	mm	205.00	205.00	205.00	266.00	205.00	205.00	266.00
	D	mm	9.70	9.70	9.70	9.70	9.70	9.70	9.70
	E	mm	6.53	6.53	6.53	6.53	6.5	6.53	6.53
	F	mm	30.00	30.00	30.00	50.80	30.00	30.00	50.80
	G	mm	40.40	40.40	40.40	40.40	40.40	40.40	40.40
UM: Under mass production									
UD: Under development (N-TEC () = Converted figure: JIS to N-TEC)									
Graphic View			Top View				Side View		
									